

**Di-LOG**  
...measurably better

## **DL2080**

### **Cable Locator Set**



- Locates Underground Cables
- Traces Cables in Walls
- Auto or Manual Signal Strength Adjust
- Non contact Voltage Indication
- Operates on Live and Dead Cables
- Auto Power Off

- Voltage 12, 50, 120, 230 & 400V,
- Tracing Depth 0 - 2.5M
- Non contact Voltage Detection 0 - 0.4M
- Frequency Range 0 - 60 Hz
- Output Signal 125 Hz
- EN61010-1, CAT III 300V

[www.dilog.co.uk](http://www.dilog.co.uk)

**Tel: 0800 018 9112 Fax: 0800 018 6711**

# SPECIFICATIONS

## DL2080

Measurement	Range
Voltage	12, 50, 120, 230 & 400V
Frequency Range	0 - 60 Hz
Output Signal	125 Hz
Tracing Depth	0 - 2.5 M Wall/Underground
Mains Voltage Detection	0 - 0.4 M
Safety	EN61010 - 1
Over Voltage Protection	CAT III 300V

## Miscellaneous

Supplied with 1 x 9V battery & 2 x AAA  
Dimensions: 192(H) x 61(W) x 37(D) mm  
Weight: 180g

**All Di-log Multimeters  
supported by a  
2 Year Warranty**

**C**

EMC & LVD  
EN: 50081-1, 50082-1  
EN: 61010-1, EN 61010-02-031

Di-log Test Equipment  
Unit 28 Wheel Forge Way  
Trafford Park  
Manchester  
M17 1EH

Sales: (0161) 877 0322  
Fax: (0161) 877 1614  
Email: sales@dilog.co.uk