

Di-LOG
...measurably better

DL6507

AC Leakage Clamp Meter



- Leakage from 10uA
- Max/Min Button
- Auto Power Off
- Bargraph
- Zero function
- 30mm Clamp
- Complete With Holster

- AC Leakage from 10uA to 100mA
- AC Voltage to 400V
- Resistance to 400 Ω
- Continuity from 0 to 400 Ω
- Auto Ranging

www.dilog.co.uk

Tel: 0800 018 9112 Fax: 0800 018 6711

SPECIFICATIONS

AC Current

Range	Resolution	Accuracy 50/60 Hz	40Hz-1kHz
0 - 40mA	10uA	± 1.5% rdg + 3dgts	± 2.0% rdg + 5 dgts
0 - 400mA	100uA	± 1.5% rdg + 3dgts	± 2.0% rdg + 5 dgts
0 - 4A	1mA	± 1.5% rdg + 3dgts	± 2.0% rdg + 5 dgts
0 - 40A	10mA	± 1.5% rdg + 3dgts	± 2.0% rdg + 5 dgts
0 - 50A	100mA	± 1.5% rdg + 5dgts	± 2.0% rdg + 5dgts
0 - 60A	100mA	± 3.0% rdg + 5dgts	± 3.5% rdg + 5dgts

AC Voltage

Range	Resolution	Accuracy 50 / 60 Hz	40Hz-1kHz
0 - 400V	0.1V	± 1.0% rdg + 3dgts	± 2.0% rdg + 4dgts

Resistance

Range	Resolution	Accuracy 50 / 60 Hz	Overload protection
400.0Ω	0.1Ω	± 1.0% rdg + 3dgts	600VAC

Continuity

Range	Resolution	Beep	Overload protection
0- 400Ω	0.1Ω	<40Ω	600VAC

Miscellaneous

Supplied with 1 x 1.5V LR6 battery (alkaline)
Dimensions: 183(H) x 63.6(W) x 35.6(D) mm
Weight: 190g

**All Di-log Clampmeters
supported by a
2 Year Warranty**



EMC & LVD
EN: 50081-1, 50082-1
EN: 61010-1, EN 61010-02-031

Di-log Test Equipment
Unit 28 Wheel Forge Way
Trafford Park
Manchester
M17 1EH

Sales: (0161) 877 0322
Fax: (0161) 877 1614
Email: sales@dilog.co.uk