



369A910 17th Edition and PAT Check Box

The only check box to provide comprehensive verification of 17th Edition and PAT test equipment. The Powercheck tests for full earth continuity, insulation, resistance, RCD trip time, RCD trip current, touch current and flash test verification.

Rugged and robust drop proof enclosure
Tests to BS 7671/ EN 61577 & IEE code of practice
NICEIC & IET performance
Colour coded for ease of use
Compatible with all installation and PAT testers.

369A910

Installation Functions Measurement	Range
Earth Continuity	0.5 Ω and 2 Ω
Insulation Resistance	0.25 M Ω , 0.5 M Ω , 1.0 M Ω
Earth Loop	Loop, Loop+ 1 Ω , Loop+180 Ω
RCD	10mA, 30mA, 100mA
Test Voltage	240 V AC test output
PAT Functions	
Earth Continuity	0.2 Ω and 2 Ω
Insulation Resistance	500 K Ω , 1 M Ω , 2 M Ω
PE Conductor Current	0.1 mA, 0.25 mA, 0.5 mA
Flash Test Current	0.5 mA, 1 mA, 1.5 mA
Power supply	230 V AC
Dimensions	210 x 145 x 83 mm
Weight	1kg

Accessories



LK240
3 wire fused lead set for Loop & RCD testers (FL1073 for 9073/9083P).



PSL/UK
Mains lead for Loop & RCD Testers (ML9073 for 9073/9083P).



LS3W9073
3 wire fused lead for 9073/9083P Supplied with 3 interchangeable prods and croc clips. Will suit all MFT's with 4 mm connectors.



TC144
Briefcase style carry case (for 3 units) with shoulder strap.



ML9073
Mains lead for Multi function testers (9073/9083P).



1189
Accessory set for 8986 Earth resistance tester.



TL1000
Standard unfused 4mm shuttered connectors to suit all types of instruments Supplied with croc clips.



DL1203
Carry case c/w shoulder harness for 9083P MFT.