

PL107 Non Contact Voltage Detector

- Contact –free visual and audible indication of AC voltages between 50-600 V
- Clear, omnidirectional flashing LED
- Quick and accurate detection of cable breaks
- Detects microwave leakage
- Detection of blown fuse
- On/off switch avoids nuisance buzzing and extends battery life

Price **£9.95**



PL107

| | |
|----------------------|-------------------------|
| Indication | 1 LED, buzzer |
| Voltage range | 50 –600 V AC |
| Frequency | 50-500 Hz |
| Overvoltage category | Cat 111/600 V |
| Power supply | 2 x 1.5 V AAA batteries |
| Dimensions | 140 x 25 x 21 mm |
| Weight | 50 g |

DL112 Voltage Indicator

The DL112 is a convenient pen sized tester which combines the latest digital technology with an advanced sensor to detect high and low voltage and continuity.

- AC Voltage indication from 12 to 600 V AC
- Audible/visual indication
- Adjustable sensitivity for phase detection
- Quick and accurate detection of cable breaks
- Continuity checking from 0 to 80 Mohms
- Featuring new work light

Price **£14.95**



DL112

| | |
|-----------------------|---------------------|
| Indication | 1 LED, buzzer |
| Voltage range | 120 –600 V AC |
| Continuity | 0 – 80 Mohm |
| Frequency | 50-500 Hz |
| Over voltage category | Cat 111/600 V |
| Power supply | 4 x L1154 batteries |
| Dimensions | 150 x 28 x 28 mm |
| Weight | 38 g |

PL105 Voltage Indicator

- Detects AC/DC voltage from 120V to 400 V
- Automatic AC/DC selection
- Automatic polarity indication
- Frequency range from 0-60Hz
- No battery required
- LED display

Price **£14.95**



PL105

| | |
|----------------------|-----------------------------------|
| Display | 4 LED's (120, 230, 400, polarity) |
| Voltage range | 120 to 400 V |
| Frequency | 0-60 Hz |
| Overvoltage category | Cat 111/400 V |
| Power supply | Direct from circuit under test |
| Dimensions | 168 x 30 x 30 mm |
| Weight | 80 g |

PL102 Voltage and Continuity Tester

- LED display
- Rugged double moulded case
- Automatic switching from voltage to continuity testing
- AC/DC voltage measurement from 12 to 690 V
- Acoustic single pole voltage measurement
- No battery required (even for continuity test), the unit is charged from the mains
- Audible and visual continuity indication

Price **£34.95**
 Calibration **£29.00**



PL102

| | |
|----------------------|--|
| Display | 8 LED's (12, 24, 50, 120, 230, 400, 690 V) |
| Voltage range | 12 to 690 V AD/DC |
| Continuity | 0 to 800 Kohm |
| Frequency | 0 to 60 Hz |
| Overvoltage category | Cat III/700 V |
| Power supply | charged from mains |
| Dimensions | 230 x 53 x 45 mm |
| Weight | 210 g |